



Anziehvorschrift für Zylinderkopf		707.860 passend für / suitable for adaptable à / adaptable a Toyota	 Das Original
Tightening Instructions for Cylinder Head			
Instructions de serrage pour culasse			
Prescripciones de apriete para culatas			
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete	
			
708.270 M 9 x 84/98			
Anziehen/ Tightening/ Serrage/ Apriete	Mot. 4 E-FE * 22 Nm 44 Nm ➤ 90°	Mot. 5 E-FE * 25 Nm 45 Nm ➤ 90°	
Zeichenerklärung / Explanations / Explication / Explicacion			
* ★ □ ● ➤	neue Zylinderkopf-schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor			
Ø: 75,5 mm			
Mot: 4E-FE, 5E-FE 1,3 ltr.-1,5 ltr. 55-66 kW (75-90 PS) Corolla 1992-2000 Paseo 1995-1999 Starlet 1996-1999			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*707.860*	