

Pro-Line Diesel Filter Additive

Description

Cleans the fuel system and injectors in high concentrations. Makes the engine easier to start and quieter to run. Protects the entire fuel system against corrosion and improves the lubrication properties of the fuel. For improved fuel atomization due to cleaner nozzles. This saves fuel, ensures better combustion and reduces the risk of damage.



Properties

- outstanding corrosion protection
- guarantees low fuel consumption
- guarantees optimum combustion
- boosts the cetane number
- cleans the fuel system
- eliminates diesel knocking
- reduces deposits

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Base	additives dissolved in carrier fluid
Density at 15 °C	0,82 g/cm ³
Color / appearance	clear, slightly yellowish to slightly reddish
Flash point	63 °C
Regulation on Flammable Liquids Class (Germany)	A III
Pour point	-35 °C
Odor	characteristic
Form	liquid
Viscosity at 40 °C	<7 mm ² /s

Areas of application

Suitable for all diesel engines. Use when changing the diesel fuel filter. Quantity to use: 500 ml. Suitable for HVO and XTL diesel.

Application

When changing the diesel fuel filter add to the filter housing intended for this purpose so that the filter is filled with the additive, the engine can start immediately and bubbles are avoided in the fuel system. Add residual amount of the additive to the tank. By using the additive, contact with potentially carcinogenic diesel fuel can be prevented.

Available pack sizes

500 ml Can sheet metal	20458 BG-DE-PL
500 ml Can sheet metal	21953 DE-EN-ES-IT-PT